

StarVedia IC502w

Pan/Tilt IP Network Camera



Plug&Play MPEG4 wireless IP cameras

With 3GPP/ISMA support

The StarVedia IC502w pan/tilt IP Network Camera is designed with the “user-friendly” idea deep in mind. The user can install the StarVedia IC502w easily on his/her home network and then access the IP Camera anywhere in the world through the accompanied video management software-CamView without setting some complicated DNS name or changing the router’s settings. It’s just a plug & play action.

With 3GPP/ISMA support, users can see the video of the IP camera on any 3G mobile phone anywhere, anytime. The big difference is that there is software for downloading to the mobile phone so that the fixed IP address is not needed for the IP camera. The video settings including frame rate, resolution and bandwidth could be different for PC monitoring and mobile viewing.

With pan/tilt support, users can monitor the video in a much larger viewing angle range.

For indoor surveillance and remote monitoring, the StarVedia IC502w provides the best image quality in its class, and excellent performance. The StarVedia IC502w IP Camera also provides the best bandwidth efficiency, it offers 640x480 resolution,

30 fps frame rate, real MPEG4 image compression ability. The built-in microphone enables remote users to not only view, but also listen for additional monitoring options.

The NAS storage function can easily turn any NAS device to a NVR device. The schedule function provides full scheduling of email/ftp sending, motion detection and NAS recording event. With the built-in Web server, the StarVedia IC202w IP Cameras can also be managed from a standard web browser on a Windows computer. With the ActiveX support, users can also see the video display on the Windows IE browser.

The StarVedia IC502w IP Camera provides both wireless IEEE 802.11 b/g and wired Ethernet network interfaces for flexible installation. It supports the WEP and WPA (Wi-Fi Protected Access) security modes to provide the best security for wireless networks.

The StarVedia IC502w IP Camera provides motion detection function. Users can easily setup this function and receive the notification with the snapshot images through email and/or ftp when some motion events are detected.

The StarVedia IC502w IP camera is ideal for securing small businesses, home offices and residences over a local area network and/or the Internet.

Features

- Easily access the camera from anywhere in the world via the ID/password (Through accompanied video management software, no complicated DNS settings needed)
- 3GPP/ISMA support
- Dual video streaming with separate frame rate/resolution/bandwidth settings for PC and mobile.
- Wide range Pan/tilt motion control.
- 802.11 b/g wireless with WEP and WPA security support
- Connect up to 20 users simultaneously
- Supports enhanced MPEG-4 compression
- Supports resolution of up to 640x480 pixels at 30 fps.
- Free video management software CamView accompanied for easy access and multi-camera management.
- View video from your Wireless or wired Ethernet network
- ActiveX video display in Microsoft IE browser.
- Motion Detection and E-mail/FTP notification
- Synchronize the system time through NTP protocol.

- Built-in Web server for managing via standard web browser.
- Built-in micro-SD card interface for video storage on SD card.
- Built-in microphone for synchronized audio.
- Event scheduling.
- NAS storage access.
- Online Firmware upgrade, will enter safe mode when power is off during critical firmware upgrade point.
- Watchdog function to prevent system failure.

Specifications

Models	StarVedia IC502w
Power	DC 5V, 2A
Processors	RISC CPU, hardware video processing and compression.
Network interface	Ethernet 10BaseT/100BaseTX, Auto-MDIX, RJ-45
Wireless interface	IEEE 802.11g 6 - 54 Mbps IEEE 802.11b 1 - 11 Mbps Transmit power: 14.5dBm typically @ 802.11g 17.5dBm typically @ 802.11b Receiver sensitivity: 54Mbps: Typical -73dBm @ 10% PER 11Mbps: Typical -86dBm @ 10% PER Antenna gain: 1.8 dBi
Pan/Tilt control	Pan range 130° (-65° ~ 65°) Tilt range 90° (0° ~ 90°) Auto pan mode Auto patrol mode
Image sensor	RGB VGA 1/4 inch CMOS Automatic exposure control, automatic white balance, automatic gain control, automatic brightness control.
Light sensitivity	0.2 Lux
Lens	3.2 mm, F2.0, viewing angle: 60.3°, fixed iris. focus range: 30 cm to infinity
D/I D/O interface	1 D/I for alarm detection 1 D/O for alarm triggering
Micro-SD card interface	Micro-SD card interface for local video storage The supported Micro SD-Card capacity is up to 16G bytes.
Buttons	One reset button, to factory default settings
Indicators	One LED for internet connection status indication One LED for Ethernet connection indication Enable/disable – web configurable
Video compression	MPEG-4 Part 2 (ISO/IEC 14496-2) with motion detection, profiles: Simple Profile, level 0-3
Frame rate	Up to 30 fps in all resolutions
Video streaming	MPEG-4 Separate frame rate/resolution/bandwidth settings

for PC and mobile.

Video settings	Resolution: VGA(640x480), QVGA(320x240), QQVGA(160x120) Bandwidth : 64k, 128k, 256k, 512k, 768k, 1M, 1.2M, 1.5M bps Frame rate : 1~5, 10, 15, 20, 25, 30 fps
Audio	Built-in microphone for audio monitoring Audio compression: MP2 audio, AMR-NB for 3GPP/ISMA(RTSP streaming)
Security	Web management username/password protection Video display ID/password protection WiFi WEP and WPA security mode
Installation, management and maintenance	Installation tool on CD and Web-based configuration Automatic configuration backup and restore Video management software-CamView for video access and multi-camera management Firmware upgrades via FTP
Minimum Web browsing and management software requirements	Built-in web server for standard web browser access Pentium 4(or equivalent AMD) CPU 1.0 GHz or higher, 1 GB RAM
Supported protocols	IPv4, HTTP, TCP, ICMP, RTSP, RTP, UDP, RTCP, SMTP, SNTP, FTP, DHCP, ARP, DNS, PPPoE, etc.
Accessories (included)	Power adaptor, RJ45 ethernet cable, quick installation guide, CD with installation tool/software and User's Manual, ID/Password card.
Video management software	Surveillance application for viewing and archiving up to 16 cameras
Users	Up to 20 simultaneous unicast users (depends on video settings)
Alarm and event management	Events triggered by video motion detection Notification/upload of JPEG images over FTP and/or email
Dimensions (HxWxD) and weight	120 x 91 x 84 mm, 350 g, camera body only.
Approvals	EMC - CE, FCC Part 15 Subpart B Class B Wireless RF - CE, FCC Part 15 Subpart C Power supply: CE, FCC, UL, EN 60950
Operating conditions	0-50 °C

Humidity 20 - 80% RH (non-condensing)